24-Inch Drawer Microwave

\$1,799 - \$1,899





DMR24M977WS/DA – Silver Stainless \$1,799 DMR24M977WM/DA – Graphite Stainless \$1,899

Features & Benefits

- · Motorized drawer
- · 10 preset modes
- · Smart moisture sensor
- · Multi-sequence cooking
- · Automatic start
- Keep warm
- · Electronic control panel


747 1 1 4 0 D				
Weights & Dimensions				
NET WEIGHT (LBS.)		72		
SHIPPING WEIGHT (LBS.)		84		
PRODUCT DIMENSIONS (W X H X D IN INCHES)		23 % x 15 % x 23 % ₄		
STANDARD CUTOUT REQ (W X H X D IN INCHES)	UIRED	22 ½ x 15 % x 23 ½		
FLUSH CUTOUT REQUIRE (W X H X D IN INCHES)	D	24 % (min.) to 24 ½ (max.) x 16 % x 23 ½		
Technical Details				
ELECTRICAL REQUIREMENTS		120V, 60 Hz, 15A		
Warranty				
FULL COVERAGE		2 Years		
Controls				
CONTROL TYPE		Glass Touch		
СГОСК		Yes		
CHILD LOCK		Yes		
Microwave Oven				
MICROWAVE CAPACITY (CU. FT.)		1.2		
MICROWAVE POWER		950W		
SENSOR COOK		Yes		
CONVECTION		No		
LIGHTING		Halogen		
Accessories (Optional)				
ADMRF24S	Flush Installation Kit, Silver Stainless \$69		\$69	
ADMRF24M	Flush Installation Kit, Graphite Stainless \$79			

24-Inch Drawer Microwave

\$1,799 - \$1,899



Product Dimensions		
A - ANTI-TIP BLOCK LENGTH (IN)	6	
B - ELECTRICAL OUTLET LOCATION (IN)	-	
C - ANTI-TIP BLOCK (IN)	-	
D - OUTLET LOCATION HEIGHT (IN)	5	
E - ANTI-TIP BLOCK WIDTH (IN)	3 ½	
F - OUTLET LOCATION WIDTH (IN)	4	
G - CUTOUT-OPENING WIDTH (IN)	22 1/8	
H - CUTOUT FLOOR TO BLOCK BOTTOM (IN)	14 ¹³ / ₁₆	
I - MINIMUM OVERLAP ALLOWANCE, SIDES (IN)	7/8	
J - MINIMUM CUTOUT DEPTH (IN)	23 ½	
K - MINIMUM OVERLAP ALLOWANCE (IN)	³ / ₁₆	
L - NOMINAL COUNTERTOP HEIGHT (IN)	36	
M - MINIMUM OVERLAP ALLOWANCE, BOTTOM (IN)	1/8	
N - MINIMUM CABINET WIDTH (IN)	24	
O - CUTOUT HEIGHT (IN)	15 %6	



Product Dimensions		
A - OVERALL CHASSIS WIDTH (IN)	21 %	
B - WIDTH OF CHASSIS NOTCH (IN)	4 11/16	
C - HEIGHT OF CHASSIS NOTCH (IN)	1 3/4	
D - CHASSIS DEPTH (IN)	21 7/8	
E - MICROWAVE FACE WIDTH (IN)	23 1/8	
F - MICROWAVE FACE HEIGHT (IN)	15 %	
G - CHASSIS HEIGHT (IN)	14 1%32	
H - DOOR FACE THICKNESS (IN)	1 %4	
I - AUTOMATIC DRAWER-OPEN DEPTH (IN)	15	
J - CHASSIS NOTCH WIDTH (IN)	4	

