

## Volume Control Capabilities

FCC ID: A3LSMF956U

Conversational gain with hearing aids: 16 dB

Conversational gain without hearing aids: 19 dB

**Note:** Conversational gain is the acoustic output level of speech from this handset relative to the acoustic level present in a face-to-face conversation between two people 1 meter apart. This phone is hearing-aid compatible and has volume control tested pursuant to FCC waiver DA 23-914.

**Codec and air interface combinations that have passed frequency response and distortion/noise tests.**

Codec	Air Interface
EVS-NB 24.4 kbps, EVS-WB 24.4 kbps	VoLTE, VoNR, VoWiFi

**Codec and air interface combinations that have passed conversational gain tests.**

Codec	Air Interface
FR V1, FR V2, HR V1	GSM
AMR-NB 4.75~12.2 kbps, AMR-WB 6.6~23.85 kbps	WCDMA
AMR-NB 4.75~12.2 kbps, AMR-WB 6.6~23.85 kbps, EVS-NB 5.9~24.4 kbps, EVS-WB 5.9~128 kbps	VoLTE, VoNR, VoWiFi

**Codec and air interface combinations that have not been tested.**

Codec	Air Interface
EVS-SWB 9.6~128 kbps	VoLTE, VoNR, VoWiFi
OPUS 6~75 kbps (Google Meet)	All air interfaces

Frequency bands exempt from HAC testing: 6000-7125 MHz, 24.25-25.25 GHz, 27.5-28.35 GHz, 37-40 GHz



QR code for  
Samsung use  
Printed in Korea  
GH68-56174A