

Self-service out of the box with Windows OS

Introducing the Samsung Kiosk with Windows OS: a compact, modern and eye-catching kiosk to provide reliable performance in any business location. Samsung Kiosk offers a variety of customer payment options including credit card, barcode, QR code and NFC, along with a built-in printer system with no additional peripherals needed. It can be installed on a countertop, on a floor stand, or be mounted on a wall. Plus, with built-in Windows 10 IoT Enterprise OS, it supports enhanced compatibility with various 3rd party devices and services to integrate and boost business operations.

Key features



Windows 10 IoT Enterprise OS

Samsung Kiosk operating on Windows enables flexible connection with versatile devices and services, making it suitable for a wide array of business use cases.



Intel® Core™ Processors

Powered by 11th Gen Intel® Core™ Processor, Samsung Kiosk built on Windows OS features high performance computing power for flexible, stable, and enhanced capabilities.



All-in-One Solution

Samsung Kiosk is an all-in-one solution without the need for an external PC.



Modular Functionality

Samsung Kiosk provides a variety of payment options including credit card, barcode, QR code and NFC, along with a built-in printer.



Stylish Look

Samsung Kiosk's stylish, compact design blends naturally into any store interior.



Optional Stand

Along with optional stand, Samsung Kiosk offers three installation types — countertop, floor stand and wall-mounting — for optimized space saving.

Specifications

Model				KM24C-3		
Diagonal Size			nal Size	24"		
			ре		ADS	
	Panel	Resolution		FHD (1,920 x 1,080)		
		Brightness (Typ.)		250cd (without glass)		
		Contrast Ratio (Typ.)		1,000:1 (without glass) 178/178		
		Viewing Angle (H/V) Response Time (G-to-G)		1767 178 14ms (Typ.)		
		Operation Hour		16/7		
	Touch	Туре		Capative		
	Sound	Speaker Type		Built in Speaker (3W x 1)		
		WiFi		Wi-Fi USB Adapter Included		
	Dienlau	Input	Video		N/A	
Display Part	Display Connectivity	Output	USB Touch Out	USB x1 (Service purpose) Touch Out x1 (Service purpose)		
			ection	One connect port (44 Pin)		
		External	Control	N/A		
			Orientation Portrait			
		Special	H/W		ept Canada, India, CIS;Russia/Ukraine/Uzbekistan/Ka	
		Special	Platform	Celeron	i3	i5
			Processor On Chin Cacho	6305E 1.8GHz Dual-Core CPU	i3-1115G4E 2.2GHz Dual-Core CPU	i5-1145G7E 1.5GHz Quad-Core CPU
		Internal Player (Embedded H/W)	On-Chip Cache Memory	4MB Intel® Smart Cache	6MB Intel® Smart Cache	8MB Intel® Smart Cache
	F		Clock Speed	1.8GHz	2.2GHz	1.5GHz
	Features		Main Memory	8GB, LPDDR4X, 4266Mbps		
			Interface	Graphic resolution: 1,920 x1,080 Output resolution: 1,920 x1,080 (Scale up from graphic processing result.) 256GB SSD N/A Windows 10 IoT Enterprise LTSC (Microsoft)		
			Graphics			
			Storage IO Ports			
			Operating System			
			Set	334.4 (W) x 547.9 (H) x 48.8 (D) mm / 13.1 (W) x 21.5 (H) x 1.9 (D) in.		
	Mechanical Spec	Dimension (mm / in.)	Package	419 (W) x 620 (H) x 122 (D) mm / 16.5 (W) x 24.4 (H) x 4.8 (D) in.		
		Weight (kg / lbs.)	Set	4.3 kg / 9.5 lbs.		
			Package	5.7 kg /12/5 lbs.		
	Connection Box Connectivity Peripheral devices	Input p: 4:-	USB	USB x 3		
		External External	ection Control	One connect port (44 Pin) RS232C x 3, RJ45 x1		
		Externat	Туре	Thermal		
		Receipt Printer	Printing speed	250mm/sec		
			Cutting	Automatic (Support Full cut, Partial cut)		
Connection Box Part			Paper support	Support 80mm paper roll, 20~83mm paper width, 0.05~0.12mm paper thickness		
		00/0	Supported dimension		1D, 2D	
		QR/Barcode Reader Readability Supported format		Mobile screen and printed barcodes UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Interleaved 2 of 5, GS1 DataBar, Codabar, QR		
		Compatible Card Readers		VeriFone, Ingenico, CloverFlex, PAX, ID Tech, Magtek, Stripe, Square, Equinox		
		EFT Terminal Cradle		Support Verifone P400/connected via RS232C		
		Dimension (mm / in.)	Set	334.4 (W) x 389.6 (H) x 236.5 (D) mm / 13.1 (W) x 15.3 (H) x 9.3 (D) in.		
	Mechanical	Difficusion (IIIIII / III.)	Package	4	28 (W) x 471 (H) x 316 (D) mm / 16.8 (W) x 2.8 (H) x 12.	4 (D) in.
	Spec	Weight (kg / lbs.)	Set		7.4 kg /16.3 lbs.	
			Package pe	9.1 kg / 20 lbs. External Adapter		
			Supply		AC100~240V 50/60Hz	
	Dower	. 31101	Max[W/h]	TBD	88	TBD
	Power	Power Consumption	Rating[W/h]	TBD	80	TBD
Assembled Set		. oner consumption	Stand-by[W/h]	TBD	0.5	TBD
		Dimension (mm / is)	BTU[W/h]	TBD 33/	300.08	TBD
	Mechanical Spec	Dimension (mm / in.) Weight (kg / lbs.)	Set Set	334.4 (W) x 733 (H) x 236.5 (D) mm / 13.1 (W) x 28.9 (H) x 9.3 (D) in. 13.2 kg / 29.1 lbs.		
		Color		GRAY WHITE		
		Protection Glass		Yes		
		Stand		Yes		
		Media Player Option Type		N/A		
		Rotation Power Cable Length		N/A 15m		
		Operating Temperature			1.5m 0°C~ 40°C	
	Operation	Humidity			10~80%	
	0+1		Stand	FloorStand		
	Others	Optional	Mount		VESA 200*200	
					Stand	
Floorstand					Stand	
	Mechanical	Dimension (mm / in.)	Set	450 (W) x 929.7 (H) x 324.3 (D) mm / 17.7 (W) x 36.6 (H) x 12.8 (D) in.		
		Package		225 (W) x 1,017 (H) x 389 (D) mm / 8.8 (W) x 40 (H) x 15.3 (D) in.		
- a a r a t		Weight (kg / lbs.)	Set		19.1 kg / 42.1 lbs.	
Floorstand	Spec	weight (kg / tbs.)	Package		21.8 kg / 48 lbs.	

Learn More

samsung.com/display samsung.com/business insights.samsung.com

Product Support Follow Us 1-866-SAM4BIZ

SAMSUNG