

It has all you need. Including affordability.

32" Affordable High-Resolution Digital Signage

Engage customers and display vivid business messaging with the Samsung SMART Signage QM32R. A high-quality yet affordable display, the QM32R features Full HD resolution, clear, sharp and colorful picture quality, and 400-nit brightness. The new slim and symmetrical design makes installation simpler, and the QM32R fits beautifully in any environment. Embedded MagicINFO 6 makes content management simple. And your captivating images will be delivered reliably, 24/7.



Key Features



Full HD for Sharp, Captivating Messages

1920 x 1080 resolution delivers sharp, FHD images that capture attention.



Slim and Symmetrical Design

The all-new slim and symmetrical design of the QM32R vastly simplifies mounting and installation, and allows seamless integration into any environment.



Powerful, All-in-One Signage Solution


The embedded MagicINFO player S6, backed by a powerful Tizen operating system, allows for easy content and display management and playback without the need for a PC.



Wi-Fi and Bluetooth Built-In

Knox Samsung Workspace Secured by Knox

Integrated Wi-Fi and Bluetooth support allows easier content management.



The Samsung QM32R supports wireless cloud service access and control of a PC, with security provided by Knox.

Attract Attention with Optimized 24/7 Performance Designed specifically for long hours of reliable operation, the Samsung QM32R is designed to attract and engage, 24/7.



3-Year Warranty


The Samsung QM32R is protected by a 3-year warranty, providing you greater peace of mind.

Samsung QM32R FHD Commercial Display

		QM32R
	Screen Size	31.5"
	Panel Type	Edge LED BLU
	Resolution	FHD (1920 x 1080)
	Brightness (Typ.)	Toolits
	Contrast Ratio (Typ.)	5000:1 178° / 178°
	Viewing Angle (H / V)	
	Response Time (G-to-G) Display Colors	8ms (Typ.) 16.7M (True Display), 1.07B (Dithered 10-bit)
	Color Gamut	16.7M (Tue Display), 1678 (Utiline a 10-bit) 72%
	Operation Hour	12°0 24/7
	Anti Glare Panel	
	Panel Orientation	Portrait / Landscape
Cassial		·
Certifications	Special Certification	IP5X
	Speaker Type	Built in Speaker (10W + 10W)
	RGB	DisplayPort1.2 (1)
	Video	HDMI 2.0 (1)
	HDCP	HDCP2.2
	Audio	Stereo Mini Jack, HDMI
	USB	USB 2.0 x 2
	RGB Video	HDMI.2.0 (Loop-Out)
	Video Audio	N/A
	Power Out	Stereo Mini Jack N/A
	USB	N/A N/A
	External Control	NVA RS232C (In / Out) Thru Stereo Jack, RJ45
	External Sensor	IR
	Tuner	No
	Wi-Fi	Yes
	Bluetooth	Yes
Power / Operation	Туре	Internal
	Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
	Power Consumption Max.(W / H)	72W/h
	Power Consumption Typical (W / H)	44W/h
	Power Consumption Rating	65W/h
	Power Consumption Typical BTU (Max)	245.5 Max.
	Power Consumption Typical Sleep Mode	0.5 W
	Power Consumption Typical Off Mode	N/A
	Set Dimensions (Inches)	28.55" x 16.52" x 1.36" 31.97" x 20.2" x 4.72"
	Package Dimensions (Inches) Set Weight (lbs)	5.197 / xC.02 x 4.72 12.97 (bs.
	Package Weight (lbs)	12.57 tos. 17.64 lbs.
	VESA Mount	200 x 200 mm
	Stand Type	Foot Stand (Optional)
	Bezel Width (mm)	0.35" (8.8mm) (U/L/R/B)
	Operating Temperature	32° -104°F
	Humidity	10 - 80%
Special Features H	Hardware	Temperature Sensor, Pivot Display, Clock Battery (168 Hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA, HDCP1.4:7EA), IP5x Rating, Wi-Fi / Bluetooth
S	Software	Auto Source Switching and Recovery, LFD Home UI, Button Lock, Hot Key Option, Plug and Play (Initial Setting)
	Processor	Cortex A72 1.7 GHz Quad-Core CPU
Player		L1 Instruction Cache: 48 KB
C	On-Chip Cache Memory	L1 Data Cache: 32 KB
		L2 Cache: 2 MB
	Clock Speed	1.7 GHz
M	Main Memory Interface	2.5 Gbj. LPDR41.5 - 8726 - 4-010
0	Graphics	Graphic Resolution: 1990 x 1080 (1990 x 1080 (1990 x 1080 x 1090
		Output Resolution: 3840 x 2160 (Result of Scale-Up from Graphic Processing) 8 GB (3.88 GB Occupied by O/S, 4.12 GB Available)
N.	Storage (FDM)	
	Multimedia	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9
10	-	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG
	Multimedia IO Ports	Video Decoder: MPEG-172/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP9, Audio Decoder: AC3 (DD), MPEG USB 2.0
0	Multimedia	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG
Safety and S	Multimedia IO Ports Operating System SSSP - MagicInfo Safety	Video Decoder: MPEG-17/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) Magicinfo 56 60950-1
Safety and S	Multimedia IO Ports Operating System SSSP - MagicInfo Safety Environment	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) Magicinfo 56 60950-1 ENERGY STAR 8.0, Epeat
Safety and S	Multimedia IO Ports Operating System SSSP - MagicInfo Safety	Video Decoder: MPEG-17/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) Magicinfo 56 60950-1
Safety and S Environmental E Certifications S Accessories In	Multimedia IO Ports Operating System SSSP - Magicinfo Safety Environment Security Included	Video Decoder: MPEG-172/A, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) MagicInfo S6 60950-1 ENERGY STAR 8.0, Epeat 802.1x (WPA2 Enterprise): EAP-TLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries
Safety and S Environmental E Certifications Accessories	Multimedia IO Ports Operating System SSSP - MagicInfo Safety Environment Security Included Optional Stand	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) MagicInfo 56 60950-1 ENERGY STAR 8.0, Epeat 802.1x (WPA2 Enterprise): EAP-TILS, EAP-TEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries STN-1.53A0E
Safety and SEnvironmental ECertifications Accessories	Multimedia IO Ports Operating System SSSP - MagicInfo Safety Environment Security Included Optional Stand	Video Decoder: MPEG-1/2/A, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) MagicInfo S6 60950-1 ENERGY STAR 8.0, Epeat 802.1x (WPA2 Enterprise): EAP-TLS, EAP-FTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries STN-L3240E WMN4070SE
Safety and SEnvironmental ECertifications Accessories	Multimedia IO Ports Operating System SSSP - MagicInfo Safety Environment Security Included Optional Stand	Video Decoder: MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 Audio Decoder: AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) MagicInfo 56 60950-1 ENERGY STAR 8.0, Epeat 802.1x (WPA2 Enterprise): EAP-TILS, EAP-TEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries STN-1.53A0E

Connectivity

- 1. USB1 (1.0A)
- 2. HDMI In 1 (ARC)
- 3. RJ45
- 4. RS232C In
- 5. HDMI In 2 (Daisy Chain In)
- 6. DP In (Daisy Chain In)
- 7. HDMI Out (Daisy Chain Out)
- 8. USB 2 (O.5A)
- 9. Audio Out
- 10. RS232C Out
- 11. IR In







ProCare

Samsung ProCare Indoor Display Solutions

- Fast Track with White Glove Next Business Day¹ Service
- Includes tech-assisted exchange of display: Technician removes original unit, installs replacement and ships non-working unit to Samsung
- Fast Track Next Bustiness Day Exchange
- Return shipping label provided, customer returns original unit in new unit's box
- Available on sizes 32"-85"
- 3-5 year terms available

Learn More samsung.com/business insights.samsung.com samsung.com/display **Product Support** 1-866-SAM4BIZ

Product Support Follow Us

youtube.com/samsungbizusa



SAMSUNG